




KALU

wall and ceiling light, three-headed, LED, 3000K, black, 60°

As one would expect, the LED extension of the popular KALU series guarantees the utterly free adjustment of lamp heads. Fitted with dimmable, high output LEDs, the KALU series has just become even more efficient and versatile! Available in matt black or black and white, KALU wall and ceiling light is supplied ready for direct connection to 230V mains supply.



TECHNICAL DATA

| | |
|-----------------------------------|----------------------------|
| Item no. | 1000131 |
| Number of different light outlets | 3 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Dimmable | Yes |
| Dimming technology | Leading edge,trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 1050 mA |
| Safety class | I |
| Wattage | 47 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 30 °C |
| Rated standby power | 0.5 W |
| Number of luminaires at LS B16A | 28 |
| Number of luminaires at LS C16A | 28 |
| Stroboscopic effect (SVM) | 0.03 |
| Lumen | 3400 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | black |

Light Source

| | |
|--------|---|
| 916610 |  |
|--------|---|

| | |
|----------------|---------|
| CRI | 80 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 43 cm |
| Width | 8.9 cm |
| Height | 16 cm |
| Net weight | 2.21 kg |
| Gross weight | 2.61 kg |
| BIG WHITE Page | 403 |