




CADRA recessed fitting

square, silver-grey, warm-white LED

With our CADRA series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a durable diode and available in either blue, neutral or warm white light colour. A suitable constant current driver rated at 350mA is needed to operate the CADRA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1000241	
IP Code	IP 20	
Assembly	Recessed	
Assembly details	Wall	
Secondary power / voltage	350 mA	
Safety class	111	
Wattage	1 W	
Operating efficiency (LOR)	0,89	
Lumen	60 lm	
Colour temperature	3000 Kelvin	
Color	grey	
CRI	90	
LXXBXX data	L70B50	
Service life	30000 h	
Light distribution	symmetric	
Light outlet	direct	
Width	9 cm	
Height	9 cm	
Depth	4 cm	
Net weight	0.155 kg	
Gross weight	0.208 kg	
Shape of cut-out	square	



Light Source

₫ G	Installation length	8.1 cm
	Installation width	6.9 cm
CABLE EXTENSION , for items with a 350mA plug, 1 m	Installation depth	4.5 cm
MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE		
MULTIWAY CONNEC- TOR , 3 outputs with two bridges, black, max. 350- mA		
FLUSH-MOUNTED , FRAME, for FRAME BA- SIC, FLAT FRAME BASI- C, FLAT FRAME CURVE and FRAME CURVE		
LED driver 3W , 350mA including AMP socket		
	CABLE EXTENSION , for items with a 350mA plug, 1 m MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE MULTIWAY CONNEC- TOR , 3 outputs with two bridges, black, max. 350- mA FLUSH-MOUNTED , FRAME, for FRAME BA- SIC, FLAT FRAME BA- SIC, FLAT FRAME CURVE and FRAME CURVE	CABLE EXTENSION , for Installation width Immunolity Installation depth MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE MULTIWAY CONNEC- MULTIWAY CONNEC- TOR , 3 outputs with two bridges, black, max. 350- mA FLUSH-MOUNTED , FRAME, for FRAME BASI- C, FLAT FRAME CURVE LED driver 3W , 350mA