



DORENO

round, white, 75°, 4000K

The simplicity and effectiveness of the innovative DORENO downlight is captivating. It is available in 3000K and 4000K. Equipped with a powerful, warm white LED, the downlight can be used in any lighting situation. The electrical connection is made using an exclusive LED driver.

TECHNICAL DATA

Item no.	1000310
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling, Ceiling with Acc.
Secondary power / voltage	700/1000/1050 mA
Safety class	III
Lumen	3000 lm
Colour temperature	4000 Kelvin
Beam angle	75 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Height	10.9 cm
Diameter	26 cm
Net weight	0.883 kg
Gross weight	1.254 kg
Shape of cut-out	round
Installation depth	16 cm
Installation diameter	17.5 cm

Accessories

1001267	LED driver , 700mA, 40-W, TRIAC dimmable
464168	LED DRIVER , 40W, 700-mA, incl. strain relief
464174	LED DRIVER , 40W, 700-mA, incl. strain relief, dimmable
464032	TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable