




GIMBLE OUT

inground fitting, LED, 3000K, stainless steel 316, 36°, IP67

The GIMBLE OUT 150 LED inground fitting with round bezel and transparent glass cover is equipped with an LED module. The head of the luminaire, which also contains the LED module, can be pulled out of the luminaire by 90°. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.



Tekniske data

Item no.	1000384
IP klasse	IP65/IP67
IK Vandalklasse	IK08
Slagfasthed	5 Joule
Montering	Recessed
Monterings detaljer	Ground, Ground with Acc.
Mekanisk belastning	0 t
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	600mA
IP Tæthedsgad	I
Watt	13 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	1100 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	36 °
Farve	brushed stainless steel
CRI	80
LXXBXX-data	L70B50
Højde	13.1 cm
Diameter	18 cm
Nettovægt	3.053 kg

Lyskilde

916450	
--------	---

Tilbehør

228730	CONNECTION BOX , 3-pin, IP68
1000655	Inground mounting pot , black for DASAR® PRE- MIUM and GIMBLE OUT
233792	Inground mounting pot , with cover for DASAR PREMIUM and GIMBLE OUT DN160

Bruttovægt	3.255 kg
Indbygningsdybde	17 cm
Installations diameter	15 cm
BIG WHITE side	849