




## ENOLA\_C

ceiling light, LED, 2000K-3000K Dim to Warm, white


The puristic ceiling mounted light ENOLA\_C consists of a cylindrical aluminium construction and is equipped with a high-performance COB LED with warm white light colour. The lighting atmosphere can be adjusted in an uncomplicated way using the dim-to-warm function. By the incorporated LED driver, the electrical connection is made directly to 230V mains supply. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	1000631
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Dim-to-Warm, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Level of inrush current	10 A
Duration of inrush current	40 $\mu$ s
Lumen	900 lm
Colour temperature	2000-3000 Kelvin
Beam angle	35 °
Color	white
CRI	90
LXXBXX data	L70B50
Service life	30000 h
Light distribution	rotational symmetric
Light outlet	direct
Height	12 cm

## Light Source

916619	 The logo for AGF, consisting of the letters 'A' and 'G' stacked vertically in a small white box, followed by a larger orange arrow pointing right containing the letter 'F'.
<b>Diameter</b>	10 cm
<b>Net weight</b>	0.656 kg
<b>Gross weight</b>	0.804 kg