# APONI 90

**outdoor floor stand, LED, 3000K, anthracite, IP65**

With the aluminium APONI 90 floor stand, the opalescent PC illumination surface is closed off with an aluminium cap. With protection class IP55, it is suitable for outdoor use. A connection box is optionally available for simplified installation. The luminaire, which comes in two sizes, is connected directly to the 230V mains power supply because of the dimmable LED constant current driver. The APONI series also includes wall lights and can therefore be used universally.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1000682 |
| **IP Code** | IP 65 |
| **Assembly** | Surface |
| **Assembly details** | Ground |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Secondary power / voltage** | 500 mA |
| **Safety class** | I |
| **Wattage** | 6.3 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Level of inrush current** | 10 A |
| **Duration of inrush current** | 40 µs |
| **Stroboscopic effect (SVM)** | 0.03 |
| **Lumen** | 520 lm |
| **Colour temperature** | 3000 Kelvin |
| **Color** | anthracite |
| **CRI** | 80 |
| **LXXBXX data** | L70B50 |
| **Service life** | 30000 h |
| **Height** | 90 cm |

## Light Source

| | |
|---|---|
| 916573 | E |

## Accessories

| | |
|---|---|
| 228730 | CONNECTION BOX , 3-pin, IP68 |

| | |
|---|---|
| **Diameter** | 7.2 cm |
| **Net weight** | 1.599 kg |
| **Gross weight** | 2.363 kg |
| **BIG WHITE Page** | 666 |