




## Q-LINE CL

LED Indoor surface-mounted ceiling light, 2m, BAP, white, 4000K

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



## TECHNICAL DATA

Item no.	1000694
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	93 W
Level of inrush current	30 A
Duration of inrush current	40 $\mu$ s
Stroboscopic effect (SVM)	0.08
Lumen	4600 lm
Colour temperature	4000 Kelvin
Beam angle	30 °
Color	white
CRI	90
UGR $\leq$	10
LXXBXX data	L70B50
Service life	25000 h

## Light Source

916460	
--------	---

<b>Light distribution</b>	axis symmetric
<b>Light outlet</b>	direct
<b>Length</b>	200 cm
<b>Width</b>	6 cm
<b>Height</b>	6 cm
<b>Net weight</b>	4.135 kg
<b>Gross weight</b>	4.93 kg
<b>BIG WHITE Page</b>	253