




KALU

wall and ceiling light, QPAR111, single-headed, black, max. 75W

The puristic design of the KALU ceiling light is the guarantee of completely free direction of the lamp head, and is optionally equipped with QPAR111 halogen lamps or suitable LED lamps. The light can also be dimmed which offers even more installation possibilities. Available in several colour versions KALU ceiling light is supplied ready for direct connection to 230V mains supply.



TECHNICAL DATA

| | |
|-----------------------------|-------------------------|
| Item no. | 1000702 |
| Socket | GU10 |
| Lamp | QPAR111 |
| Number of sockets | 1 |
| Lamps included | No |
| Tilt range | 90 ° |
| Horizontal rotation range | 350 ° |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Safety class | I |
| Wattage | 75 W |
| Maximum ambient temperature | 40 °C |
| Color | black |
| Light outlet | direct |
| Length | 15 cm |
| Width | 9 cm |
| Height | 18 cm |
| Net weight | 0.509 kg |
| Gross weight | 0.705 kg |

Recommended lamp

| | |
|---------|--|
| 1005274 | QPAR111 GU10 , transparent LED light, 8W 2700K CRI90 38° |
| 1005298 | LED lamp , QPAR111 GU10 12W 680lm 3000K CRI90 55° Dimmable |
| 1005297 | LED lamp , QPAR111 GU10 12W 670lm 2700K CRI90 55° Dimmable |
| 1005299 | LED lamp , QPAR111 GU10 12W 750lm 4000K CRI90 55° Dimmable |