




ALAMEA

recessed ceiling light, LED, 4000K, white, 29,4W

The ALAMEA recessed ceiling light for commercial applications and applications needing clear light properties. Available with a black or white housing, the ALAMEA is equipped with a powerful 29.4 Watt LED. The LED insert, which is available in two light colours, is telescopic and adjustable, and can therefore be flexibly directed. A suitable LED constant current driver is required to operate the recessed fitting. This luminaire has a built-in LED module.



TECHNICAL DATA

| | |
|---------------------------|----------------|
| Item no. | 1000793 |
| Rotating or tilting | tiltable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Lumen | 2750 lm |
| Colour temperature | 4000 Kelvin |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 35000 h |
| Light distribution | axis symmetric |
| Light outlet | direct |
| Length | 24.6 cm |
| Width | 15.6 cm |
| Height | 11.3 cm |
| Net weight | 2.216 kg |
| Gross weight | 2.474 kg |
| Shape of cut-out | square |
| Installation length | 22.5 cm |

| | |
|--------------------|---------|
| Installation width | 13 cm |
| Installation depth | 11.3 cm |

Accessories

| | |
|---------|---|
| 1001114 | LED driver , 700mA, 40-W, dimmable |
| 464168 | LED DRIVER , 40W, 700-mA, incl. strain relief |
| 464174 | LED DRIVER , 40W, 700-mA, incl. strain relief, dimmable |
| 464032 | TCI LED DRIVER , 50VA, 350-1050mA, dip switch, incl. strain relief, DALI dimmable |