




Q-LINE PD

LED indoor pendant, 1m, BAP, white, 4000K

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



TECHNICAL DATA

Item no.	1000932
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	46 W
Level of inrush current	30 A
Duration of inrush current	40 μ s
Stroboscopic effect (SVM)	0.16
Lumen	2300 lm
Colour temperature	4000 Kelvin
Beam angle	30 °
Color	white
CRI	90
UGR \leq	10
LXXBXX data	L70B50
Service life	25000 h

Light Source

916460	
--------	---

Light distribution	axis symmetric
Light outlet	direct
Length	100 cm
Width	6 cm
Height	6 cm
Pendant length	150 cm
Net weight	2.52 kg
Gross weight	3.043 kg
BIG WHITE Page	293