





KAMUELA ECO

recessed ceiling light, LED, 3000K, black, 38°, dimmable, IP65

The KAMUEL ECO LED recessed fitting is equipped with an integrated premium LED. The recessed light is made of aluminium and plastic and is fitted with a warm-white LED. The fire-resistant recessed fitting series is fire-resistant for at least 90 minutes (BS 476-21). An appropriate dimmable constant current driver is integrated for operating the recessed fitting, and is therefore suitable for direct connection to 230 Volts. This luminaire contains built-in LED lamps and is available with different housing colours.



Tekniske data

Item no.	1001015
IP klasse	IP65
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	Leading edge, trailing edge
Primær spænding	220-240V ~50Hz
IP Tæthedsggrad	II
Watt	6 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	500 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	38 °
Farve	black
CRI	84
LXXBXX-data	L70B50
Højde	7.1 cm
Diameter	8.8 cm
Nettovægt	0.265 kg

Lyskilde

916388	
--------	---

Bruttovægt	0.314 kg
Indbygningsdybde	7.1 cm
Installations diameter	7 cm
BIG WHITE side	236