


## DOLIX OUT QPAR51

square, silver-grey

The DOLIX OUT high-voltage recessed ceiling light is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. Thanks to the already incorporated GU10 high-voltage socket, the DOLIX OUT recessed ceiling light is ready for direct connection to 230V mains supply.



## TECHNICAL DATA

Item no.	1001171
Socket	GU10
Number of sockets	1
IP Code	IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	50 W
Color	grey
Light outlet	direct
Length	8.8 cm
Width	8.8 cm
Height	11 cm
Net weight	0.197 kg
Gross weight	0.231 kg
Shape of cut-out	round
Installation depth	11 cm
Installation diameter	6.8 cm
BIG WHITE Page	235

## Recommended lamp

1005273	QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36°
1005079	LED lightbulb QPAR51 , GU10, 3000K, white
1005076	LED lightbulb QPAR51 , GU10, 2700K, white
1005082	LED lightbulb QPAR51 , GU10, 4000K, white