




DOLIX OUT QPAR51

square, matt chrome

The DOLIX low-voltage recessed ceiling ring is made from aluminium and is equipped with a glass for protection against splashing water. Rated IP65 it can be used outdoors or in damp areas. To operate the recessed fitting, a matching transformer for low-voltage halogen lamps is required.



Tekniske data

Item no.	1001172
Sokkel	GU10
Antal fatninger	1
IP klasse	IP65
IK Vandalklasse	IK02
Slagfæsthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Primær spænding	220-240V ~50/60Hz
IP Tæthedsggrad	II
Watt	50 W
Farve	silver
Længde	8.8 cm
Bredde	8.8 cm
Højde	11 cm
Nettovægt	0.199 kg
Bruttovægt	0.232 kg
Indbygningsdybde	11 cm
Installations diameter	6.8 cm
BIG WHITE side	235

Anbefalet lyskilde

1005273	QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36°
1005079	LED lightbulb QPAR51 , GU10, 3000K, white
1005076	LED lightbulb QPAR51 , GU10, 2700K, white
1005082	LED lightbulb QPAR51 , GU10, 4000K, white