




## VALETO® LED PANEL

LED Indoor recessed ceiling light, 600x600mm, UGR<19

The LED VALETO PANEL comes in two sizes and is a modern, space-saving solution for an efficient type of basic lighting. Because the light is fully compatible with Valeto Smart, the light colour can be set to between 2700 and 6500 Kelvin. With this product you reach a pleasant, homogeneous and glare-free lighting feeling. An aperture angle under 19° is achieved here.



## TECHNICAL DATA

Item no.	1001250
Number of different light outlets	1
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Dim-to-Warm, Zigbee
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	950 mA
Safety class	II
Wattage	39.55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Network rated standby power	0.29 W
Level of inrush current	56 A
Duration of inrush current	1.82 µs
Stroboscopic effect (SVM)	0.02
Lumen	3600-4000 lm
Colour temperature	2700-6500 Kelvin
Beam angle	95 °
Color	white
CRI	80

## Light Source

916627		UGR $\leq$	19
		LXXBXX data	L70B50
		Service life	25000 h
		Length	59.5 cm
		Width	59.5 cm
		Height	1.1 cm
		Net weight	3.191 kg
		Gross weight	3.79 kg