




AKALO 83

DL, indoor recessed ceiling light, 3000K 4000K 5700K adjustable, white

The AKALO luminaire is a recessed ceiling light for universal use indoors. The light temperature is switchable in all versions. The electrical connection is made directly to the 230V mains supply.



Tekniske data

Item no.	1001264
Antal lysåbninger	1
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	Leading edge, trailing edge
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	120mA
IP Tæthedsgard	II
Watt	9 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	800/880/850 lm
Farvetemperatur	3000/4000/5700 Kelvin
Spredningsvinkel	90 °
Farve	white
CRI	80
UGR ≤	28
LXXBXX-data	L70B50
Højde	6.5 cm

Lyskilde

916471	
--------	---

Diameter	11 cm
Nettovægt	0.19 kg
Bruttovægt	0.24 kg
Indbygningsdybde	7 cm
Installations diameter	9.2 cm
BIG WHITE side	237