



## L-LINE 60 LED

wall and ceiling light, IP44, 3000K, 820lm, silver

The L-LINE 60 wall and ceiling light is fitted with a warm-white LED module and, thanks to its 1500 lm of LED power, is the ultimate LED solution for primary room lighting. The smooth and elegant L-LINE LED is available in white, silver-grey and grey colour versions. Thanks to the integrated LED driver, the luminaire can be connected directly to the 230V mains supply.

### TECHNICAL DATA

Item no.	1001300
IP Code	IP 44
Assembly	Surface
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	10 W
Level of inrush current	10 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.3
Lumen	820 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	silver
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	symmetric
Light distribution 2	symmetric
Light outlet	direct
Light outlet 2	indirect

## Light Source

916534	
--------	---

<b>Width</b>	61.8 cm
<b>Height</b>	7 cm
<b>Depth</b>	7 cm
<b>Net weight</b>	1.106 kg
<b>Gross weight</b>	1.472 kg
<b>BIG WHITE Page</b>	341