




LED PANEL ROUND

pendant, white, 360LED, 40W, dimmable 1-10V, 3000K


The LED PANEL pendant is available in three different light colours and impresses with its ultra-flat shape and its powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which ensures homogeneous and glare-free illumination. The built-in LED driver allows direct connection to a mains supply of 100V to 240V.



TECHNICAL DATA

Item no.	1001344
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	42 W
Level of inrush current	8.5 A
Duration of inrush current	25 µs
Stroboscopic effect (SVM)	0.01
Lumen	3150 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	white
UGR ≤	22
LXXBXX data	L70B50
Service life	30000 h
Height	3.2 cm
Diameter	60 cm
Pendant length	200 cm
Net weight	4.433 kg

Light Source

916602	 The AEG logo, consisting of the letters 'A' and 'G' stacked vertically on the left, and a yellow arrow pointing to the right containing the letter 'E'.	Gross weight	5.984 kg
--------	---	---------------------	----------