


## TEC KALU double

white/black 60° 3000K, incl. 3-circuit adapter


The futuristic 240V TEC KALU with an appropriate adapter for the 3-circuit 240V track system has individually rotating and swivelling lamp heads with warm-white and dimmable premium LEDs. The built-in LED driver is located within the main structure. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.



## TECHNICAL DATA

Item no.	1001420
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Track Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	31 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Rated standby power	0.5 W
Stroboscopic effect (SVM)	0.03
Lumen	1900 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h

## Light Source

916610		<b>Light distribution</b>	rotational symmetric
		<b>Light outlet</b>	direct
		<b>Length</b>	29.5 cm
		<b>Width</b>	17 cm
		<b>Height</b>	15.5 cm
		<b>Net weight</b>	1.686 kg
		<b>Gross weight</b>	2.137 kg