




PANEL

1200x300mm LED Indoor surface-mounted ceiling light, 4000K, silver-grey

The LED PANEL, which is available in several different light and housing colours, provides a modern and space-saving solution for an efficient form of basic lighting. With its high lumen output and a UGR value of less than 19, it provides a pleasant, homogeneous and glare-free lighting atmosphere, even for workstations. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1001509
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	40
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	45 W
Level of inrush current	9 A
Duration of inrush current	50 µs
Stroboscopic effect (SVM)	0.03
Lumen	3400 lm
Colour temperature	4000 Kelvin
Beam angle	90 °
Color	grey
CRI	90
UGR ≤	19
LXXBXX data	L70B50
Service life	30000 h

Light Source

916385	
--------	---

Light distribution	symmetric
Light outlet	direct
Length	119.5 cm
Width	29.5 cm
Height	5 cm
Net weight	4.474 kg
Gross weight	5.376 kg
BIG WHITE Page	275