




LED FLOOD LIGHT

matt white, 30W, warm white, 100°

Powerful FLOOD LIGHT spot for illuminating areas and spaces. With a tiltable installation bracket and protection class IP65, the spot is suitable for outdoor installation on the wall, ceiling or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. An earth spike is available as an option for simplified floor installation.



TECHNICAL DATA

Item no.	1001643
Rotating or tilting	tiltable
IP Code	IP 65
Impact resistance class	IK 04
Impact resistance	0.5 Joule
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	760 mA
Safety class	I
Wattage	32 W
Maximum ambient temperature	40 °C
Lumen	2200 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	symmetric
Light outlet	direct
Length	25 cm

Width	8 cm
Height	32 cm
Net weight	2.692 kg
Gross weight	2.984 kg

Accessories

234340	Wall bracket , for Outdoor Beam and MILOX flood-light, black, 50cm
234350	WALL BRACKET , for SPOODI 15/20/31, black, 80 cm
900011	PLASTIC EARTH SPIKE , black, length 17.5cm