




LIPA CL

LED Outdoor surface-mounted ceiling light, IP54, white, 3000/4000K


SLV LIPA robust, water-protected surface-mounted solution. Round wall and ceiling light made from aluminium. Thanks to its IP54 protection class it is suitable for outdoor use. The opal illuminated area has an LED light source beneath it which can be switched between warm and cool white, and is enclosed by the painted housing. The luminaire comes in several colour versions and is connected directly to the 230V mains supply thanks to its built-in LED driver.



TECHNICAL DATA

Item no.	1001855
IP Code	IP 54
Impact resistance class	IK 05
Impact resistance	0.7 Joule
Assembly	Surface
Assembly details	Ceiling, Wall
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	21 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	30 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.01
Lumen	1600 lm
Colour temperature	3000/4000 Kelvin
Beam angle	120 °
Color	white

Light Source

916401		LXXBXX data	L70B50
		Service life	30000 h
		Height	6.3 cm
		Diameter	28 cm
		Net weight	1.953 kg
		Gross weight	2.394 kg