


MEDO 30 EL

LED indoor recessed ceiling light, frameless version, white, 3000/4000K

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



TECHNICAL DATA

Item no.	1001901
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	14 W
Maximum ambient temperature	40 °C
Lumen	1500/1600 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR ≤	25
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	9.5 cm
Diameter	28 cm
Net weight	1.272 kg

Light Source

916562	
--------	---

Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1007229	LED driver 25W 150-700- mA DALI TOUCH
1007228	LED Driver 20W 350mA dimmable
1007225	LED Driver 20W 350mA

Gross weight	1.826 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	29 cm
BIG WHITE Page	170