




AROSA

1,25m, TRIAC PD, LED indoor pendant, aluminium, 3000K

The AROSA pendant, available in two lengths, is equipped with white, black or anodised aluminium housing as desired. A PMMA diffuser, which is used on the upper and lower light outlet, provides glare-free lighting characteristics. The integrated warm-white LEDs provide a high degree of light output. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



TECHNICAL DATA

Item no.	1001942
Number of different light outlets	2
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	32 W
Ambient temperature	25 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	8.2 A
Duration of inrush current	170 µs
Lumen	1700 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	aluminium
CRI	80
LXXBXX data	L70B50

Service life	40000 h
Light distribution	axis symmetric
Light outlet	direct - indirect
Length	125.3 cm
Width	2.7 cm
Height	4.2 cm
Pendant length	200 cm
Net weight	2.137 kg
Gross weight	2.934 kg