




LIPSY 50 Dome

LED Outdoor surface-mounted wall and ceiling light, white, IP44, 3000/4000K


With their timeless and discreet design, the LIPSY DOME series of wall and ceiling lights are a popular lighting solution for a wide range of applications. The steel and acrylic glass luminaires come in a variety of housing sizes. The wide beam characteristic creates homogeneous lighting in combination with the powerful LED module. The built-in driver makes direct connection to a 230V mains voltage supply possible. The light colour of the product can be switched between 3000K and 4000K.



TECHNICAL DATA

Item no.	1002022
IP Code	IP 44
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	30 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.01
Lumen	2500/2700 lm
Colour temperature	3000/4000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
Service life	50000 h
Height	12.4 cm
Diameter	40 cm
Net weight	1.007 kg

Light Source

916360		Gross weight	1.55 kg
		BIG WHITE Page	423