




ALMINO PD

quad, LED outdoor surface-mounted ceiling light,
UGR<19, grey IP65 4000K

With the ALMINO luminaire family we are providing ceiling lights and wall lights which can be optionally suspended for professional use with the highest demands. Thanks to the robust casing and the built-in LEDs, the luminaires provide efficient basic lighting with limited direct glare (UGR<19) and are therefore particularly suitable for industrial areas, warehouses and logistics areas. A suspension set and mounting brackets are available as optional accessories.



TECHNICAL DATA

Item no.	1002194
Number of different light outlets	1
IP Code	IP 65
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling with Acc.
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1200 mA
Safety class	II
Wattage	190 W
Minimum ambient temperature	-30 °C
Maximum ambient temperature	60 °C
Level of inrush current	17.3 A
Duration of inrush current	68.8 µs
Lumen	24000 lm
Colour temperature	4000 Kelvin
Beam angle	50 °
Color	grey
CRI	80
UGR ≤	19
LXXBXX data	L70B10
Service life	50000 h

Light distribution	axis symmetric
Light outlet	direct
Length	85.6 cm
Width	19.6 cm
Height	10.9 cm
Net weight	4.859 kg
Gross weight	6.129 kg