




## GIMBLE IN 150

Indoor LED recessed ceiling light, white, 3000K

The Premium LED installed in the GIMBLE IN 150 recessed ceiling light gives off a particularly warm light. Of course, the light outlet of this recessed ceiling light is tiltable. With a CRI value of greater than or equal to 90, the GIMBLE IN 150 is ideal for true-colour lighting of rooms. This should be your choice of recessed ceiling light if colour rendering is very important to you. This recessed ceiling light is sustainable and low-maintenance thanks to the anticipated service life of 30,000 hours.



### TECHNICAL DATA

|                           |                         |
|---------------------------|-------------------------|
| Item no.                  | 1002888                 |
| Rotating or tilting       | rotary Bar and tiltable |
| IP Code                   | IP 20                   |
| Assembly                  | Recessed                |
| Assembly details          | Ceiling                 |
| Secondary power / voltage | 700 mA                  |
| Safety class              | III                     |
| Wattage                   | 24.5 W                  |
| Lumen                     | 2300 lm                 |
| Colour temperature        | 3000 Kelvin             |
| Beam angle                | 36 °                    |
| Color                     | white                   |
| CRI                       | 90                      |
| LXXBXX data               | L70B50                  |
| Service life              | 30000 h                 |
| Light distribution        | rotational symmetric    |
| Light outlet              | direct                  |
| Risk Group                | 1                       |
| Height                    | 13.5 cm                 |
| Diameter                  | 16.2 cm                 |
| Net weight                | 0.582 kg                |
| Gross weight              | 0.83 kg                 |

## Light Source

|        |   |
|--------|---|
| 916434 |  |
|--------|---|

## Accessories

|         |  |
|---------|--|
| 1002424 | LED driver MEDO 400 ,<br>dimmable DALI/1-10V |
|---------|--|

|                       |         |
|-----------------------|---------|
| Installation depth    | 13.5 cm |
| Installation diameter | 15 cm   |