




## MEDO RING 60 DALI

Indoor LED pendant, black, 3000K


As well as having an appealing design, the modern MEDO RING impresses with efficient and powerful LED modules that are also dimmable. The aluminium frame is fitted with an acrylic glass cover which provides bright and uniform illumination. Its 1.5 metre pendant length makes it ideal for rooms with high ceilings. The built-in LED driver makes direct connection to a 120V to 240V mains supply possible.



## TECHNICAL DATA

Item no.	1002890
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2, Touch
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	34 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
Network rated standby power	0.5 W
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	2200 lm
Colour temperature	3000 Kelvin
Beam angle	105 °
Color	black
CRI	80

## Light Source

916532		<b>UGR <math>\leq</math></b>	22
		<b>LXXBXX data</b>	L70B50
		<b>Service life</b>	20000 h
		<b>Light distribution</b>	rotational symmetric
		<b>Light outlet</b>	direct
		<b>Risk Group</b>	1
		<b>Height</b>	8 cm
		<b>Diameter</b>	60 cm
		<b>Pendant length</b>	150 cm
		<b>Net weight</b>	5.112 kg
		<b>Gross weight</b>	6.219 kg
		<b>BIG WHITE Page</b>	167