



LIPSY 40 DRUM DALI CW

LED Indoor surface-mounted wall and ceiling light, white, 3000/4000K

Because of their timeless and discreet design, the wall and ceiling lights in the LIPSY DRUM DALI series are a popular lighting solution for a wide range of applications. The steel and acrylic glass luminaires come in a variety of housing sizes. The wide beam characteristic creates homogeneous lighting in combination with the powerful LED module. The built-in DALI-compatible LED driver makes it possible to connect directly to a 230V mains power supply. The light colour of the product can be switched between 3000K and 4000K.

TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 1002940 |
| IP Code | IP 44 |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 18 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 15 A |
| Duration of inrush current | 500 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 2100/2300 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 120 ° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |

Light Source

| | | | |
|--------|---|-----------------------|----------|
| 916526 |  | Risk Group | 0 |
| | | Height | 8.8 cm |
| | | Diameter | 35 cm |
| | | Net weight | 0.854 kg |
| | | Gross weight | 1.407 kg |
| | | BIG WHITE Page | 426 |