



LIPSY 50 DRUM DALI CW

LED Indoor surface-mounted wall and ceiling light, white, 3000/4000K

Because of their timeless and discreet design, the wall and ceiling lights in the LIPSY DRUM DALI series are a popular lighting solution for a wide range of applications. The steel and acrylic glass luminaires come in a variety of housing sizes. The wide beam characteristic creates homogeneous lighting in combination with the powerful LED module. The built-in DALI-compatible LED driver makes it possible to connect directly to a 230V mains power supply. The light colour of the product can be switched between 3000K and 4000K.

TECHNICAL DATA

Item no.	1002941
IP Code	IP 44
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	21 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	15 A
Duration of inrush current	500 µs
Stroboscopic effect (SVM)	0.01
Lumen	2450/2600 lm
Colour temperature	3000/4000 Kelvin
Beam angle	120 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	30000 h

Light Source

916360		Risk Group	0
		Height	9.6 cm
		Diameter	40 cm
		Net weight	1.063 kg
		Gross weight	1.735 kg
		BIG WHITE Page	426