






FLATT POLE 100

Outdoor LED floor stand, 3000 K, IP65, anthracite

Would you like a floor stand which can be effortlessly mounted on the floor? This should have a safety class of at least IP 65, and therefore be thus dustproof and protected from water spray from various directions. Our FLATT POLE 100 has IP 65 and is therefore brilliant for lighting a path or the terrace. Are you looking for amazing light for your outdoor area? This is provided by the built-in Premium LED of the FLATT POLE 100 floor stand. Incidentally, the FLATT POLE 65 gives you even more advantages as a part of the SLV family. Because we have been successful with our lighting concepts for 40 years, and keep setting the bar higher for ourselves and our products.



TECHNICAL DATA

Item no.	1002958
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Primary nominal voltage	100-240V ~50/60 Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	10 W
Ambient temperature	40 °C
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
Level of inrush current	2 A
Level of inrush current Duration of inrush current	2 A 1000 μs
Duration of inrush current	1000 μs
Duration of inrush current Lumen	1000 μs 400 lm
Duration of inrush current Lumen Colour temperature	1000 μs 400 lm 3000/4000 Kelvin
Duration of inrush current Lumen Colour temperature Color	1000 μs 400 lm 3000/4000 Kelvin anthracite/anthracite
Duration of inrush current Lumen Colour temperature Color CRI	1000 μs 400 lm 3000/4000 Kelvin anthracite/anthracite
Duration of inrush current Lumen Colour temperature Color CRI Service life	1000 µs 400 lm 3000/4000 Kelvin anthracite/anthracite 80 30000 h
Duration of inrush current Lumen Colour temperature Color CRI Service life Risk Group	1000 μs 400 lm 3000/4000 Kelvin anthracite/anthracite 80 30000 h
Duration of inrush current Lumen Colour temperature Color CRI Service life Risk Group Length	1000 μs 400 lm 3000/4000 Kelvin anthracite/anthracite 80 30000 h 1 18 cm



Light Source

916440	A E
Accessories	
228730	CONNECTION BOX , 3-pin, IP68

Net weight	4.64 kg
Gross weight	5.258 kg
BIG WHITE Page	793