




## NOBLO I

### Indoor LED surface-mounted ceiling light 2700K white

NOBLO rotating and tilting LED spotlight for surface mounting on walls and ceilings. The luminaire impresses with its slim design and is therefore ideal for modern lighting concepts. The luminaire is made from aluminium and equipped with a Premium LED module. The luminaire is available in three housing colours with two or three light outlets.



## TECHNICAL DATA

Item no.	1002970
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Operating efficiency (LOR)	0,8
Number of luminaires at LS B16A	128
Number of luminaires at LS C16A	160
Level of inrush current	3.5 A
Duration of inrush current	120 µs
Stroboscopic effect (SVM)	0.4
Lumen	620 lm
Colour temperature	2700 Kelvin

## Light Source

916369	
--------	---

<b>Beam angle</b>	36 °
<b>Color</b>	white
<b>CRI</b>	80
<b>LXXBXX data</b>	L70B50
<b>Service life</b>	30000 h
<b>Risk Group</b>	1
<b>Length</b>	9 cm
<b>Width</b>	10.5 cm
<b>Height</b>	12.7 cm
<b>Net weight</b>	0.313 kg
<b>Gross weight</b>	0.405 kg
<b>BIG WHITE Page</b>	401