


NOTAPO I

Indoor recessed wall light 3000K white

Aluminium recessed wall light NOTAPO I WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO I recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.



Tekniske data

Item no.	1002979
IP klasse	IP20
Montering	Recessed
Monterings detaljer	Wall,Wall with Acc.
Sekundær strøm / spænding	700mA
IP Tæthedsgad	III
Watt	2.2 W
Max omgivelsestemperatur	40 °C
Lumen	6 lm
Farvetemperatur	3000 Kelvin
Farve	white
CRI	90
LXXBXX-data	L70B50
Bredde	3.6 cm
Højde	10.5 cm
Dybde	3.8 cm
Nettovægt	0.086 kg
Bruttovægt	0.126 kg
Indbygnings længde	10 cm
Indbygningsbredde	2.8 cm
Indbygningsdybde	5 cm
BIG WHITE side	241

Lyskilde

954799	
--------	---

Tilbehør

1007213	LED DRIVER , 10W, 700-mA, PHASE, incl. strain relief
1007216	LED driver 3W , 700mA incl. strain relief
1007229	LED driver 25W 150-700-mA DALI TOUCH
1002981	NOTAPO I and II WL , installation frame