




NOTAPO II

Indoor recessed wall light 3000K white

Aluminium recessed wall light NOTAPO II WL. The invisibly installed LED emits its light indirectly onto the surface to be illuminated. This makes glare-free illumination of walkways and staircases possible, for example. The NOTAPO II recessed fitting is available with a white housing. An installation frame and a mounting box for installation in masonry are optionally available. This luminaire contains built-in LED lamps.



Tekniske data

Item no.	1002980
IP klasse	IP20
Montering	Recessed
Monterings detaljer	Wall, Wall with Acc.
Sekundær strøm / spænding	700mA
IP Tæthedsgard	III
Watt	2.2 W
Max omgivelsestemperatur	40 °C
Lumen	6 lm
Farvetemperatur	3000 Kelvin
Farve	white
CRI	90
LXXBXX-data	L70B50
Bredde	3.6 cm
Højde	18 cm
Dybde	3.8 cm
Nettovægt	0.114 kg
Bruttovægt	0.166 kg
Indbygnings længde	17.3 cm
Indbygningsbredde	2.8 cm
Indbygningsdybde	5 cm
BIG WHITE side	241

Lyskilde

954799	
--------	---

Tilbehør

1007213	LED DRIVER , 10W, 700-mA, PHASE, incl. strain relief
1007216	LED driver 3W , 700mA incl. strain relief
1007229	LED driver 25W 150-700-mA DALI TOUCH
1002981	NOTAPO I and II WL , installation frame