



## SENSER 24

### Indoor LED recessed ceiling light round white 3000K

The SENSER recessed fitting made from aluminium is available in white and silver-grey, and with a round or square shade. The rigid Premium LED insert produces homogeneous base illumination over a wide area thanks to its extensive beam angle. If you are looking for a recessed ceiling light with a shallow installation depth, SENSER is just the job.

## TECHNICAL DATA

|                            |             |
|----------------------------|-------------|
| Item no.                   | 1003010     |
| IP Code                    | IP 20       |
| Impact resistance class    | IK 02       |
| Impact resistance          | 0.2 Joule   |
| Assembly                   | Recessed    |
| Assembly details           | Ceiling     |
| Secondary power / voltage  | 500 mA      |
| Safety class               | III         |
| Wattage                    | 13 W        |
| Ambient temperature        | 25 °C       |
| Operating efficiency (LOR) | 0,7         |
| Lumen                      | 1140 lm     |
| Colour temperature         | 3000 Kelvin |
| Color                      | white       |
| CRI                        | 90          |
| UGR ≤                      | 27          |
| LXXBXX data                | L70B50      |
| Service life               | 50000 h     |
| Risk Group                 | 1           |
| Height                     | 2 cm        |
| Diameter                   | 21.5 cm     |
| Net weight                 | 0.308 kg    |

## Light Source

|         |   |
|---------|---|
| 1814258 |  |
|---------|---|

## Accessories

|         |  |
|---------|--|
| 1007226 | LED driver 21W 500mA                     |
| 1007227 | LED driver 20W 350mA-<br>/500mA PHASE    |
| 1007229 | LED driver 25W 150-700-<br>mA DALI TOUCH |

|                       |          |
|-----------------------|----------|
| Gross weight          | 0.386 kg |
| Shape of cut-out      | round    |
| Installation depth    | 3 cm     |
| Installation diameter | 20.5 cm  |
| BIG WHITE Page        | 223      |