




PANEL 60 DALI

Indoor LED surface-mounted ceiling lights round grey 3000K


The PANEL 60 DALI ceiling light is available in several different light colours and impresses with its ultra-flat design and powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which provides homogeneous and glare-free illumination. The built-in DALI-compatible operating device makes direct connection to a mains power supply of 100V - 240V possible.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 1003042 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Number of through-wires | 40 |
| Primary nominal voltage | 120-277V ~50/60Hz |
| Secondary power / voltage | 1000 mA |
| Safety class | I |
| Wattage | 43 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Network rated standby power | 0.3 W |
| Level of inrush current | 30 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 3150 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 110 ° |
| Color | grey |
| CRI | 80 |

Light Source

| | | | |
|--------|---|-----------------------|----------|
| 916602 |  | UGR ≤ | 22 |
| | | LXXBXX data | L70B50 |
| | | Service life | 30000 h |
| | | Height | 5.5 cm |
| | | Diameter | 60 cm |
| | | Net weight | 4.603 kg |
| | | Gross weight | 5.8 kg |
| | | BIG WHITE Page | 275 |