




PANEL 60 DALI

Indoor LED surface-mounted ceiling lights round grey 4000K

The PANEL 60 DALI ceiling light is available in several different light colours and impresses with its ultra-flat design and powerful, dimmable LED modules. The aluminium frame is fitted with an acrylic glass cover which provides homogeneous and glare-free illumination. The built-in DALI-compatible operating device makes direct connection to a mains power supply of 100V - 240V possible.



Tekniske data

Item no.	1003043
IP klasse	IP20
Montering	Surface
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	DALI
Antal lamper ved videresløjfning	40
Primær spænding	120-277V ~50/60Hz
Sekundær strøm / spænding	1000mA
IP Tæthedsgard	I
Watt	43 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	3350 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	110 °
Farve	matt gray
CRI	80
UGR ≤	22
LXXBXX-data	L70B50
Højde	5.5 cm
Diameter	60 cm

Lyskilde

916481		Nettovægt	4.573 kg
		Bruttovægt	5.857 kg
		BIG WHITE side	275