




I-PENDANT PRO DALI

Indoor LED pendant UGR<19 grey 4000K

With the I-PENDANT PRO DALI, which is available with several different light colours, we are providing a modern and space-saving solution for an efficient kind of basic lighting with the additional possibility of DALI control. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting sensation. The electrical connection is made via the built-in LED power supply directly to a 100-240V mains power supply.



Tekniske data

Item no.	1003051
IP klasse	IP20
Montering	Surface
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	DALI
Primær spænding	120-277V ~50/60Hz
Sekundær strøm / spænding	1000mA
IP Tæthedsgard	II
Watt	43 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	3800 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	90 °
Farve	matt gray
CRI	80
UGR ≤	19
LXXBXX-data	L70B50
Længde	119.5 cm
Bredde	29.5 cm
Højde	1.3 cm

Lyskilde

916310	
--------	---

Pendellængde	170 cm
Nettovægt	5.035 kg
Bruttovægt	6.284 kg
BIG WHITE side	289