




LED PANEL 620x620

Indoor LED recessed ceiling light white 4000K
UGR<19

The LED PANEL for grid ceilings, which can be switched between two light colours, is a modern and space saving solution for an efficient kind of basic lighting. You achieve a pleasant, homogeneous and glare-free lighting sensation with this product, with an aperture angle of less than 19°.



Tekniske data

Item no.	1003074
IP klasse	IP20
Montering	Recessed
Monterings detaljer	Ceiling, Ceiling with Acc.
Sekundær strøm / spænding	1050mA
IP Tæthedsgard	III
Watt	35 W
Lumen	4000 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	120 °
Farve	white
CRI	90
UGR ≤	19
LXXBXX-data	L70B50
Længde	61.7 cm
Bredde	61.7 cm
Højde	0.9 cm
Nettovægt	3.345 kg
Bruttovægt	4.205 kg
Indbygningsdybde	5 cm
BIG WHITE side	243

Lyskilde

916349	
--------	---

Tilbehør

1006197	LED driver , 40W 1050-mA DALI dimmable with RF interface LED driver white DALI
158791	CEILING PLATE , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, white
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1002425	LED driver MEDO 600 , dimmable DALI/1-10V
464804	LED DRIVER , 40W, 1050mA, triac dimmable
158799	SUSPENSION SET , for LED PANEL, I-VIDUAL and I-VIDUAL LED PANEL, steel wire and Y-wire suspension