



SUPROS PD

Indoor LED pendant, round, white, 3000K, 60° reflector, CRI90, 2600lm

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.

TECHNICAL DATA

Item no.	1003276
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	750 mA
Safety class	I
Wattage	31 W
Ambient temperature	25 °C
Level of inrush current	18.6 A
Duration of inrush current	240 µs
Stroboscopic effect (SVM)	0.01
Lumen	2600 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	90
LXXBXX data	L70B50
Service life	50000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1

Light Source

791822	
--------	---

Accessories

114104	REFLECTOR , for SU-PROS, 40°, incl. glass and fixing ring
114102	REFLECTOR , for SU-PROS, 20°, incl. glass and fixing ring

Height	18.5 cm
Diameter	12.7 cm
Pendant length	200 cm
Net weight	1.645 kg
Gross weight	1.759 kg