




SUPROS MOVE

Indoor LED recessed ceiling light white round 4000K
60° CRI90 2700lm

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

| | |
|----------------------------|-------------------------|
| Item no. | 1003312 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 750 mA |
| Safety class | II |
| Wattage | 31 W |
| Ambient temperature | 25 °C |
| Level of inrush current | 18.6 A |
| Duration of inrush current | 240 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 2700 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| LXXBXX data | L70B50 |
| Service life | 50000 h |
| Light distribution | rotational symmetric |
| Light outlet | direct |

Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

Accessories

| | |
|--------|---|
| 114104 | REFLECTOR , for SU-PROS, 40°, incl. glass and fixing ring |
| 114102 | REFLECTOR , for SU-PROS, 20°, incl. glass and fixing ring |

| | |
|-----------------------|----------|
| Risk Group | 1 |
| Height | 17 cm |
| Diameter | 19.5 cm |
| Net weight | 1.51 kg |
| Gross weight | 1.666 kg |
| Shape of cut-out | round |
| Installation depth | 11.5 cm |
| Installation diameter | 18 cm |