




EASY-INSTALL SLIM LED

DL, indoor recessed ceiling light, 4000K, aluminium matt

This LED recessed spotlight from SLV generates much more than just light. The EASY-INSTALL SLIM LED spot is a lighting experience which starts with the first touch, impresses during installation and is a source of enthusiasm in everyday life. The quality of this luminaire becomes evident as soon as you start to unpack it. The high-quality aluminium and the workmanship of the materials set standards in terms of haptic perception. Thanks to the minimal installation depth, the ceiling spot can be installed in many different situations, and the IP44 protection class also makes use in wet rooms possible. The flexible connecting element between the driver and the LED, which makes installation a piece of cake, makes a significant difference. The spotlight can be removed and uncoupled in an uncomplicated way if painting work is required, for example. The benefits are rounded off by the through-wiring capability (spring clip provided) and the capability of direct installation in all kinds of insulating material, since residual heat is led away towards the front. It is not just electricians, installers and tradespeople who swear by the flexibility of this LED recessed fitting. Available with different surface colours and colour temperatures, the dimmable (TRIAC C, phase control) EASY-INSTALL SLIM LED impresses with a service life of an incredible 50,000 hours. The light outlet can be swivelled by 30° so that the user can always point the light in the required direction. And all of this including a 5-year warranty, of course. You can look forward to your product with the customary SLV quality!

Tekniske data

Item no.	1003338
IP klasse	IP44
Montering	Recessed
Monterings detaljer	Ceiling
Dæmpbar	Ja
Dæmpningstype	trailing edge
Antal lamper ved videresløjfning	20
Primær spænding	220-240V ~50/60Hz
Sekundær strøm / spænding	125mA
IP Tæthedsggrad	II
Watt	6.2 W
Lumen	510 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	35 °
Farve	aluminum
CRI	80
LXXBXX-data	L70B50
Højde	3.9 cm
Diameter	8.7 cm
Nettovægt	0.249 kg
Bruttovægt	0.302 kg
Indbygningsdybde	3.5 cm



Lyskilde

Installations diameter	7.5 cm
------------------------	--------

916363	
--------	---