




ENOLA SQUARE UP/- DOWN M

outdoor LED surface-mounted wall light anthracite

The ENOLA SQUARE and ROUND light series have a purist style, consisting of a cylindrical or square aluminium construction fitted with powerful LEDs. Thanks to the integrated CCT switch, the light colour can be altered between 3000 K and 4000 K on installation. Thanks to the integrated LED driver, the electrical connection for the light is made directly to the 230 V mains voltage. In order to cover as wide a range of applications as possible, you can opt for one or two-lamp wall lights or ceiling lights in round or square form and in different sizes. This light contains integrated LED light bulbs.



TECHNICAL DATA

Item no.	1003419
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall, Wall with Acc.
Number of through-wires	37
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	37
Number of luminaires at LS C16A	74
Level of inrush current	10 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.07
Lumen	1660/1900 lm
Colour temperature	3000/4000 Kelvin
Beam angle	38 °

Light Source

916566	
--------	---

Accessories

1002853	Spacer set , for outdoor wall-mounted lights anthracite
1005206	ENOLA M , lens asymmetric
1005205	ENOLA M , lens 20°
1005207	ENOLA M , reflector 60°

CRI	90
LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Width	10 cm
Height	23 cm
Depth	15 cm
Net weight	1.74 kg
Gross weight	2.129 kg
BIG WHITE Page	730