





## ENOLA ROUND UP/-DOWN L

## outdoor LED surface-mounted wall light anthracite CCT 3000/4000K

The ENOLA SQUARE and ROUND series of puristic luminaires consist of a cylindrical or square aluminium construction, and are equipped with powerful LEDs. The light colour can be switched between 3000K and 4000K during installation using the built-in CCT. Because of the built-in LED driver, the electrical connection of the luminaire is made directly to a 230V mains voltage supply. In order to cover as wide a range of uses as possible, single and double headed wall lights and ceiling lights are available in round and square version in various sizes. This luminaire contains built-in LED lamps.



## **TECHNICAL DATA**

Item no.	1003441
Number of different light outlets	2
IP Code	IP 65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall, Wall with Acc.
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	55 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	300 µs
Duration of inrush current Stroboscopic effect (SVM)	1
	300 μs
Stroboscopic effect (SVM)	300 μs 0.01
Stroboscopic effect (SVM)  Lumen	300 μs 0.01 5400/6000 lm
Stroboscopic effect (SVM)  Lumen  Colour temperature	300 μs  0.01  5400/6000 lm  3000/4000 Kelvin
Stroboscopic effect (SVM)  Lumen  Colour temperature  Beam angle	300 μs  0.01  5400/6000 lm  3000/4000 Kelvin  38 °



## **Light Source**

916421	â E
Accessories	
1002853	Spacer set , for outdoor wall-mounted lights anthracite
1005263	ENOLA L , chrome reflector 60°

LXXBXX data	L70B50
Service life	30000 h
Risk Group	1
Width	14 cm
Height	33.2 cm
Depth	19 cm
Net weight	3.077 kg
Gross weight	3.843 kg
BIG WHITE Page	727