





ENOLA ROUND L

outdoor LED surface-mounted ceiling light anthracite CCT 3000/4000K

The ENOLA SQUARE and ROUND series of puristic luminaires consist of a cylindrical or square aluminium construction, and are equipped with powerful LEDs. The light colour can be switched between 3000K and 4000K during installation using the built-in CCT. Because of the built-in LED driver, the electrical connection of the luminaire is made directly to a 230V mains voltage supply. In order to cover as wide a range of uses as possible, single and double headed wall lights and ceiling lights are available in round and square version in various sizes. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1003442
IP Code	IP 65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	36 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	300 μs
Stroboscopic effect (SVM)	0.03
Lumen	3200/3500 lm
Colour temperature	3000/4000 Kelvin
Beam angle	38 °
Color	anthracite
CRI	90
LXXBXX data	L70B50



Light Source

916421	A E
Accessories	
1003479	Spacer set , for the ENO- LA SQUARE OUT and ROUND OUT ceiling lights in anthracite
1005263	ENOLA L , chrome reflector 60°

Service life	30000 h
Risk Group	1
Height	22.3 cm
Diameter	14 cm
Net weight	1.708 kg
Gross weight	2.089 kg
BIG WHITE Page	793