




MANA OUT WL

Wall-mounted light set grey/anthracite 11W 650lm
3000K CRI80 60° Phase cut-off

Now also available with a shade in the fashionable material concrete: the dimmable MANA OUT WL wall light is designed with a high-performance LED for a warm white light (3000 K). Thanks to its IP65 protection class rating, this aluminium and concrete outdoor light is protected in any weather. The CRI of over 80 ensures natural colour reproduction. And thanks to the already integrated LED driver, a direct connection to a 220 volt supply is possible.



TECHNICAL DATA

Item no.	1003470
Number of different light outlets	2
IP Code	IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Level of inrush current	12.4 A
Duration of inrush current	7.2 µs
Stroboscopic effect (SVM)	0.04
Lumen	650 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	grey

Light Source

916573	
--------	---

CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	axis symmetric
Light outlet	direct - indirect
Risk Group	1
Length	18.2 cm
Width	16 cm
Height	10.3 cm
Net weight	2.67 kg
Gross weight	3.317 kg
BIG WHITE Page	721