



## NUMINOS® MOVE DL M

Indoor LED recessed ceiling light white/black 2700K  
20° rotating and pivoting

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1460 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?

## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1003565                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary Bar and tiltable |
| IP Code                           | IP 20                   |
| Impact resistance class           | IK 02                   |
| Impact resistance                 | 0.2 Joule               |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 500 mA                  |
| Safety class                      | III                     |
| Wattage                           | 17.55 W                 |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 1460 lm                 |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 20 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 19                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Light distribution                | rotational symmetric    |

## Light Source

|        |   |
|--------|---|
| 791800 |  |
|--------|---|

### Accessories

|         |  |
|---------|--|
| 1004792 | NUMINOS® M , diffuser Frosted  |
| 1004069 | LED driver , 29W 500mA   |
| 1004064 | LED driver , 21-29.5W 500/600/700mA  |
| 1006459 | LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI |
| 1006143 | Numinos® M Reducing ring , round 240/120mm black   |
| 1004054 | LED driver , 20W 500mA PHASE   |
| 1006146 | Numinos® M Reducing ring , square 240/120mm white  |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006144 | Numinos® M Reducing ring , round 240/120mm white   |
| 1004793 | NUMINOS® M , diffuser Wabe   |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006145 | Numinos® M Reducing ring , square 240/120mm black  |
| 1004790 | NUMINOS® M , diffuser Ellipse  |
| 1004791 | NUMINOS® M , diffuser Prisma   |

|                       |         |
|-----------------------|---------|
| Light outlet          | direct  |
| Risk Group            | 1       |
| Height                | 9 cm    |
| Diameter              | 13.5 cm |
| Net weight            | 0.39 kg |
| Gross weight          | 0.45 kg |
| Shape of cut-out      | round   |
| Installation depth    | 10 cm   |
| Installation diameter | 12 cm   |
| <b>BIG WHITE Page</b> | 87      |