




NUMINOS® MOVE DL M

Indoor LED recessed ceiling light white/chrome 4000K
40° rotating and pivoting

The NUMINOS light system from SLV combines technology, design and functionality like no other. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE DL M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light can convince with a power consumption of 17.55 watts, luminous flux of 1660 lumens, colour temperature of 4000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



Tekniske data

Item no.	1003618
Antal lysåbninger	1
IP klasse	IP20
IK Vandalklasse	IK02
Slagfasthed	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	500mA
IP Tæthedsggrad	III
Watt	17.55 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	1660 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	40 °
Farve	white/chrome
CRI	90
UGR ≤	19
LXXBXX-data	L80B50
Højde	9 cm
Diameter	13.5 cm
Nettovægt	0.378 kg

Lyskilde

791825	
Tilbehør	
1004792	NUMINOS® M , diffuser Frosted
1004069	LED driver , 29W 500mA
1004064	LED driver , 21-29.5W 500/600/700mA
1006459	LED bridge driver , 42W, 500mA for NUMINOS®, including radio interface for RF module, DALI
1006143	Numinos® M Reducing ring , round 240/120mm black
1004054	LED driver , 20W 500mA PHASE
1006146	Numinos® M Reducing ring , square 240/120mm white
1006454	RF module Casambi for LED bridge driver , single colour
1006144	Numinos® M Reducing ring , round 240/120mm white
1004793	NUMINOS® M , diffuser Wabe
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1006145	Numinos® M Reducing ring , square 240/120mm black
1004790	NUMINOS® M , diffuser Ellipse
1004791	NUMINOS® M , diffuser Prisma

Bruttovægt	0.437 kg
Indbygningsdybde	10 cm
Installations diameter	12 cm
BIG WHITE side	87