



## NUMINOS® MOVE DL L

Indoor LED recessed ceiling light white/white 2700K  
55° rotating and pivoting

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® MOVE DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2250 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When will you choose SLV's modular variety?

## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1003644                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary Bar and tiltable |
| IP Code                           | IP 20                   |
| Impact resistance class           | IK 02                   |
| Impact resistance                 | 0.2 Joule               |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 700 mA                  |
| Safety class                      | III                     |
| Wattage                           | 25.41 W                 |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 2250 lm                 |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| LXXBXX data                       | L80B50                  |
| Service life                      | 50000 h                 |
| Light distribution                | rotational symmetric    |

## Light Source

|        |   |
|--------|---|
| 791800 |  |
|--------|---|

### Accessories

|         |  |
|---------|--|
| 1006148 | Numinos® L Reducing ring , round 240/150mm white   |
| 1006149 | Numinos® L Reducing ring , square 240/150mm black  |
| 1004062 | LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie                            |
| 1004795 | NUMINOS® L , diffuser Prisma   |
| 1004796 | NUMINOS® L , diffuser Frosted  |
| 1006460 | LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI |
| 1004794 | NUMINOS® L , diffuser Ellipse  |
| 1006150 | Numinos® L Reducing ring , square 240/150mm white  |
| 1006454 | RF module Casambi for LED bridge driver , single colour                                    |
| 1006199 | RF module Zigbee for DALI LED bridge driver , single colour                                |
| 1006147 | Numinos® L Reducing ring , round 240/150mm black   |
| 1004070 | LED driver , 40W 700mA DALI  |
| 1004797 | NUMINOS® L , diffuser Wabe   |
| 1004065 | LED driver , 30W 700mA   |

|                       |         |
|-----------------------|---------|
| Light outlet          | direct  |
| Risk Group            | 1       |
| Height                | 9.5 cm  |
| Diameter              | 16 cm   |
| Net weight            | 0.54 kg |
| Gross weight          | 0.68 kg |
| Shape of cut-out      | round   |
| Installation depth    | 10.5 cm |
| Installation diameter | 14.5 cm |
| BIG WHITE Page        | 87      |