




NUMINOS® MOVE DL L

Indoor LED recessed ceiling light white/chrome 3000K
20° rotating and pivoting

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. This also includes NUMINOS® MOVE DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 25.41 watts, luminous flux of 2200 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



Tekniske data

Item no.	1003663
Antal lysåbninger	1
IP klasse	IP20
IK Vandalklasse	IK02
Slagfaste	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	700mA
IP Tæthedegrad	III
Watt	25.41 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	2200 lm
Farvetemperatur	3000 Kelvin
Spredningsvinkel	20 °
Farve	white/chrome
CRI	90
UGR ≤	19
LXXBXX-data	L80B50
Højde	9.5 cm
Diameter	16 cm
Nettovægt	0.519 kg

Lyskilde

791822		Bruttovægt	0.653 kg
Tilbehør		Indbygningsdybde	10.5 cm
1006148	Numinos® L Reducing ring , round 240/150mm white	Installations diameter	14.5 cm
1006149	Numinos® L Reducing ring , square 240/150mm black	BIG WHITE side	87
1004062	LED driver , 21-29.5W 500/600/700mA for Numinos Downlight Serie		
1004795	NUMINOS® L , diffuser Prisma		
1004796	NUMINOS® L , diffuser Frosted		
1006460	LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI		
1004794	NUMINOS® L , diffuser Ellipse		
1006150	Numinos® L Reducing ring , square 240/150mm white		
1006454	RF module Casambi for LED bridge driver , single colour		
1006199	RF module Zigbee for DALI LED bridge driver , single colour		
1006147	Numinos® L Reducing ring , round 240/150mm black		
1004070	LED driver , 40W 700mA DALI		
1004797	NUMINOS® L , diffuser Wabe		
1004065	LED driver , 30W 700mA		