




NUMINOS® MOVE DL XL

Indoor LED recessed ceiling light black/black 4000K
20° rotating and pivoting

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of down-lights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE DL XL recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 37.4 watts, a luminous flux of 3600 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



Tekniske data

Item no.	1003745
Antal lysåbninger	1
IP klasse	IP20
IK Vandalklasse	IK02
Slagfaste	0.2 Joule
Montering	Recessed
Monterings detaljer	Ceiling
Sekundær strøm / spænding	1050mA
IP Tæthedegrad	III
Watt	37.4 W
Min omgivelsestemperatur	-20 °C
Max omgivelsestemperatur	40 °C
Lumen	3600 lm
Farvetemperatur	4000 Kelvin
Spredningsvinkel	20 °
Farve	black
CRI	90
UGR ≤	22
LXXBXX-data	L80B50
Højde	11.8 cm
Diameter	19 cm
Nettovægt	0.7 kg

Lyskilde

791850	
Tilbehør	
1006152	Numinos® XL Reducing ring , round 240/180mm white
1006151	Numinos® XL Reducing ring , round 240/180mm black
1004800	NUMINOS® XL , diffuser Frosted
1004071	LED driver 4.2-50W 1050mA DALI
1006454	RF module Casambi for LED bridge driver , single colour
1006154	Numinos® XL Reducing ring , square 240/180mm white
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004798	NUMINOS® XL , diffuser Ellipse
1006153	Numinos® XL Reducing ring , square 240/180mm black
1004059	LED driverm 40W multi mA
1006461	LED bridge driver , 42W, 1050mA for NUMINOS®, including radio interface for RF module, DALI
1004066	LED driver , 28-40W 1000mA PHASE
1004801	NUMINOS® XL , diffuser Wabe
1004799	NUMINOS® XL , diffuser Prisma

Bruttovægt	0.864 kg
Indbygningsdybde	13 cm
Installations diameter	17.5 cm
BIG WHITE side	87